



Armoured Optical Cable Fibre



DESCRIPTION

These cables are designed for direct burial application and provide excellent transmission performance & protection to fibre in variety of field environment

APPLICATION


- Long haul communication system
- Direct burial application
- Local area networks
- Can also be used in ducts where the operation environment is exceptionally severe.

FEATURES

- Protection against rodents & termites
- S-Z Stranded
- Outstanding Impact & Crush resistance
- Standard fibre counts : 2 - 48
- Available with stainless/chrome plated steel tape armour

CABLE CROSS SECTION

1. Primary Coated Optical Fibre - Single mode / Multimode
2. Tube Filling Compound - Thixotropic gel
3. Loose Tube – Polyamide/PBTP or other acceptable Thermoplastic material
4. Dummy Filler (if required) – Polyethylene
5. Central Strength Member - Fibre reinforced plastic rod
6. Water Blocking Media - Water Swellable Tape / Suitable Water Blocking Gel
7. Inner Sheath - Black Polyethylene
8. Armour - Corrugated Steel Tape.
9. Outer Sheath - Black Polyethylene



IS/ ISO 9001-2000

IS/ ISO 14001





MECHANICAL & ENVIROMENTAL CHARACTERISTICS

Tensil force (IEC 60794-1-E1)	
During installation	1.3 x W
Permanent	0.6 x W
Bending radius (IEC607494-1-E11)	
Temporary, unloaded	20D
Permanent, during installation	25D
Repeated bending (EIA-455-104)	30 times, with weight of 50N
Torsion resistance (IEC 60794-1-E7)	10 cycle with load of 400N
Crush resistance (IEC 60794-1-E3)	4000N (100 x 100mm)
Impact resistance (IEC 60794-1-E4)	25N-m
Kink resistance (IEC 60794-1-E10)	20D
Temperature range (IEC 60794-1-F1)	
Operation	-30° to +70° C
Storage	-30° to +70° C
Installation	-20° to +50° C
Spark Test (IEC 60794-1-F3)	Pass
Water Penetration (IEC 60794-1-F5)	Pass
W = Weight in Kg of 1 Km. cable	D = Diameter of cable in mm.

COLOUR CODING

Colour of fibre in Ribbon	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose & Natural Last fibre in tube will be Natural
Identification method	Marker & Tracer Blue tube/filler (Marker) Orange tube/filler(Tracer)
Other elements	Natural and/ Black

DELIVERY INFORMATION

	Upto	Upto	Upto
	24 F	48 F	96 F
Cable Weight (Nominal) – Kg / Km	226	260	180
Cable Diameter (Nominal) – mm	15.7	16.9	14.9
Supplied Length – Kms	2, 4 & 6		

Note :

1. Fibre in cable can comply to G651/G652/G652D/G655 or as desired. Properties of cabled fibre available on request.
2. The given cable cross section and characteristics will change as per specification desired by the customers.

IS/ ISO 9001-2000

IS/ ISO 14001

